

## RFQ Form

Please download this editable PDF to your computer. Once you have filled out all of the fields, save your work and send it to [ovensales@lewcoinc.com](mailto:ovensales@lewcoinc.com). Or fax a printed version to 419.625.1247

Company: \_\_\_\_\_

Contact: \_\_\_\_\_

Address: \_\_\_\_\_

City, State or Province: \_\_\_\_\_

Zip or Postal Code: \_\_\_\_\_ Country: \_\_\_\_\_

Email: \_\_\_\_\_

Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

Project Reference: \_\_\_\_\_

Timeframe for: Quote \_\_\_\_\_ Purchase \_\_\_\_\_

Pricing Requirement:  Budget  Firm

### 1. Temperature & Performance Requirements:

- 300°F (150°C) Traditional "Hot Box"
- 300°F (150°C) High-Performance Oven (*NFPA 86, Class B design. Indoor use only*)
- 450°F (232°C) High-Performance Oven (*NFPA 86, Class B design. Indoor use only*)

### 2. Is the product flammable or combustible? Yes No

a. Are you heating above the product flash point and auto-ignition temperature?  Yes  No

b. If yes, what is the flash point and auto-ignition temperature of the product?

Flash Point: \_\_\_\_\_  °F  °C  Unknown (*Consult Factory for options*)

Auto-Ignition Temperature: \_\_\_\_\_  °F  °C  Unknown (*Consult Factory for options*)

3. Type of container to be heated?  55-Gallon Drums  Totes/ IBC Tanks  
 Other: \_\_\_\_\_
4. Number of drums or totes to be heated: \_\_\_\_\_  
*Standard Drum Cabinet Capacities: 1, 2, 4, 6, 8, 12, 16, 24, 32, or 48 Drums*  
*Standard Tote Cabinet Capacities: 1, 2, 3, 4, 6, or 8 Totes*
5. Where will the equipment be installed?  Indoor  Outdoor
6. What type of configuration do you require?
- Low Profile** (plate steel floor, no spill containment – not suitable for outdoor installation)  
*Available in 1 to 12 drum capacities; not available for totes.*
  - Standard Profile** (single-level with spill containment sump)  
*Available in 1 to 16 drum, or 1 to 4 tote capacities.*
  - Multi-Level** (includes with spill containment sump)  
*Available in 8 drum (2 tote), 16 drum (4 tote), 24 drum (6 tote), 32 drum (8 tote), and 48 drum capacities.*
7. What is preferred heating medium?
- Electric:** Voltage/ Phase/ Hz \_\_\_\_\_ (Standard is 480/3/60)  
*\*NOTE: Electrically heated “hot box” models are not suitable for heating flammable or combustible materials, nor intended for installation in electrically classified areas.*
  - Saturated Steam:** Supply pressure (10-200 psi): \_\_\_\_\_
  - Hot Water:** Supply Temperature: \_\_\_\_\_  °F  °C
  - Hot Oil:** Supply Temperature: \_\_\_\_\_  °F  °C
8. If you selected saturated steam, hot oil, or hot water above, what type of temperature controls are required?
- None (*no controls*)
  - Electronic, single set-point digital temperature controller and redundant high-limit controller
  - Non-electronic, self-acting temperature controllers, limited to 150 psig, available in the following ranges:
    - 125°F - 212°F (52°C - 100°C), ½” valve
    - 158°F - 300°F (70°C - 149°C), ½” valve
9. Is a circulating fan required?  Yes  No (*Adds 15°F to minimum operating temperature*)
10. Is a vent required? (*5” diameter, damper included. Not available for outdoor installation*)  Yes  No

11. Does the equipment require any hazardous area classification? (ex. Class 1, Division 1, Group D)

---

12. Finish?  Standard alkyd enamel  Premium finish for corrosive environments

a. Color?  Blue  Gray  Custom (RAL# \_\_\_\_\_)

13. Do you require any additional options?

- Door Switch (disables heat when door is opened)
- Batch Timer (*automatically turns off heat at completion*)
- Single Pen Chart Recorder
- Steam Trap(s)
- Drum Rotator(s)
- Data Logger
- Ramp/ Soak Controller
- Stainless Steel
- Adjustable Leveling Legs
- Auxiliary Hose Access Port
  - o Quantity \_\_\_\_\_ Size \_\_\_\_\_
- Zero Speed Switch for Fans (*Only available with High-Performance Models*)
- Exhaust Fan (*Only available with High-Performance Models*)
- Third Party Inspection (*i.e. CSA, U/L, etc.*)
- Other Requirements:

**14. Will the equipment be installed in the USA or be exported?**

USA     Exported

a. If exported, please provide shipping port \_\_\_\_\_

b. If exported, do you require export crating?

Yes     No

c. Do you require a freight quote?

Yes     No

d. If a freight quote is requested, please provide a shipping address:

Same address as above

Address: \_\_\_\_\_

City, State, or Province: \_\_\_\_\_

Zip or Postal Code: \_\_\_\_\_

Country: \_\_\_\_\_

**15. Any space or door restrictions? (Most units come completely assembled)**

**Please provide any additional information, requirements, or questions:**

*Thank you for this opportunity!*