

RFQ Form

Please download this editable PDF to your computer. Once you have filled out all the fields, save your work and send it to ovensales@lewcoinc.com. Or fax a printed version to 419.625.1247

Company	y:
Contact:	
Address:	
City, Stat	te or Province:
Zip or Po	estal Code: Country:
Email:	
	Fax:
Project R	Reference:
Timefram	ne for: Quote Purchase
Pricing R	Requirement: Budget Firm
1. Temp	erature & Performance Requirements:
	300°F (150°C) Traditional "Hot Box"
	300°F (150°C) High-Performance Oven (NFPA 86, Class B design. Indoor use only)
	450°F (232°C) High-Performance Oven (NFPA 86, Class B design. Indoor use only)
2. Is the	product flammable or combustible? Yes No
a.	Are you heating above the product flash point and auto-ignition temperature? Yes No
b.	If yes, what is the flash point and auto-ignition temperature of the product?
	Flash Point: □ °F □ °C □ Unknown <i>(Consult Factory for options)</i>
	Auto-Ignition Temperature: □ °F □ °C □ Unknown (Consult Factory for
	options)
3. Type	of container to be heated? 55-Gallon Drums Totes/ IBC Tanks
-	
	per of drums or totes to be heated:
	andard Drum Cabinet Capacities: 1, 2, 4, 6, 8, 12, 16, 24, 32, or 48 Drums
St	andard Tote Cabinet Capacities: 1, 2, 3, 4, 6, or 8 Totes



5.	Where	will the equipment be installed? Indoor Outdoor
6.	Harsh	environmental factors to consider?
		Temp. above 100°F. Temp. below 35°F. Moisture/ Humidity
7.	What t	ype of configuration do you require?
		Low Profile (plate steel floor, no spill containment – not suitable for outdoor installation) Available in 1 to 12 drum capacities; not available for totes.
		Standard Profile (single-level with spill containment sump) Available in 1 to 16 drum, or 1 to 4 tote capacities.
		Multi-Level (includes with spill containment sump) Available in 8 drum (2 tote), 16 drum (4 tote), 24 drum (6 tote), 32 drum (8 tote), and 48 drum capacities.
8.	What is	s preferred heating medium?
		Electric: Voltage/ Phase/ Hz(Standard is 480/3/60)
		*NOTE: Electrically heated " hot box " models are not suitable for heating flammable or combustible materials, nor intended for installation in electrically classified areas.
		Saturated Steam: Supply pressure (20-200 psi):
		Hot Water: Supply Temperature: □ °F □ °C
		Hot Oil: Supply Temperature: □ °F □ °C
9.	If you	selected saturated steam, hot oil, or hot water above, what type of temperature controls are
	require	
		None (no controls)
		Electronic, single set-point digital temperature controller and redundant high-limit controller
		Non-electronic, self-acting temperature controllers, limited to 150 psig, available in the following
	ran	ges:
		☐ 125°F - 212°F (52°C - 100°C), ½" valve
		☐ 158°F - 300°F (70°C - 149°C), ½" valve
10	. Is a cir	culating fan required? ☐ Yes ☐ No (Adds 15°F to minimum operating temperature)
11.	. Is a ve	nt required? (5" diameter, damper included. Not available for outdoor installation) 🚨 Yes 🚨 No



a. Color? Blue Gray Custom (RAL#) 14. Do you require any additional options? Door Switch (disables heat when door is opened) Batch Timer (automatically turns off heat at completion) Steam Trap(s) Drum Rotator(s) Data Logger Ramp/ Soak Controller Stainless Steel Adjustable Leveling Legs Auxiliary Hose Access Port Quantity Size Zero Speed Switch for Fans (Only available with High-Performance Models) Exhaust Fan (Only available with High-Performance Models) U/L Inspection CSA Inspection	13. Finish	? □ Standard alkyd enamel □ Premium finish for corrosive environments
 □ Door Switch (disables heat when door is opened) □ Batch Timer (automatically turns off heat at completion) □ Steam Trap(s) □ Drum Rotator(s) □ Data Logger □ Ramp/ Soak Controller □ Stainless Steel □ Adjustable Leveling Legs □ Auxiliary Hose Access Port ○ Quantity Size □ Zero Speed Switch for Fans (Only available with High-Performance Models) □ Exhaust Fan (Only available with High-Performance Models) □ U/L Inspection □ CSA Inspection 	a.	Color? Blue Gray Custom (RAL#)
 □ Batch Timer (automatically turns off heat at completion) □ Steam Trap(s) □ Drum Rotator(s) □ Data Logger □ Ramp/ Soak Controller □ Stainless Steel □ Adjustable Leveling Legs □ Auxiliary Hose Access Port ○ Quantity Size □ Zero Speed Switch for Fans (Only available with High-Performance Models) □ Exhaust Fan (Only available with High-Performance Models) □ U/L Inspection □ CSA Inspection 	14. Do you	require any additional options?
 □ Steam Trap(s) □ Drum Rotator(s) □ Data Logger □ Ramp/ Soak Controller □ Stainless Steel □ Adjustable Leveling Legs □ Auxiliary Hose Access Port ○ Quantity Size □ Zero Speed Switch for Fans (Only available with High-Performance Models) □ Exhaust Fan (Only available with High-Performance Models) □ U/L Inspection □ CSA Inspection 		Door Switch (disables heat when door is opened)
 □ Drum Rotator(s) □ Data Logger □ Ramp/ Soak Controller □ Stainless Steel □ Adjustable Leveling Legs □ Auxiliary Hose Access Port ○ Quantity Size □ Zero Speed Switch for Fans (Only available with High-Performance Models) □ Exhaust Fan (Only available with High-Performance Models) □ U/L Inspection □ CSA Inspection 		Batch Timer (automatically turns off heat at completion)
 □ Data Logger □ Ramp/ Soak Controller □ Stainless Steel □ Adjustable Leveling Legs □ Auxiliary Hose Access Port ○ Quantity □ Size □ Zero Speed Switch for Fans (Only available with High-Performance Models) □ Exhaust Fan (Only available with High-Performance Models) □ U/L Inspection □ CSA Inspection 		Steam Trap(s)
 □ Ramp/ Soak Controller □ Stainless Steel □ Adjustable Leveling Legs □ Auxiliary Hose Access Port ○ Quantity Size □ Zero Speed Switch for Fans (Only available with High-Performance Models) □ Exhaust Fan (Only available with High-Performance Models) □ U/L Inspection □ CSA Inspection 		Drum Rotator(s)
 □ Stainless Steel □ Adjustable Leveling Legs □ Auxiliary Hose Access Port ○ Quantity □ Zero Speed Switch for Fans (Only available with High-Performance Models) □ Exhaust Fan (Only available with High-Performance Models) □ U/L Inspection □ CSA Inspection 		Data Logger
 □ Adjustable Leveling Legs □ Auxiliary Hose Access Port ○ Quantity □ Size □ Zero Speed Switch for Fans (Only available with High-Performance Models) □ Exhaust Fan (Only available with High-Performance Models) □ U/L Inspection □ CSA Inspection 		Ramp/ Soak Controller
 □ Auxiliary Hose Access Port ○ Quantity Size □ Zero Speed Switch for Fans (Only available with High-Performance Models) □ Exhaust Fan (Only available with High-Performance Models) □ U/L Inspection □ CSA Inspection 		Stainless Steel
 Quantity Size Zero Speed Switch for Fans (Only available with High-Performance Models) Exhaust Fan (Only available with High-Performance Models) U/L Inspection CSA Inspection 		Adjustable Leveling Legs
 □ Zero Speed Switch for Fans (Only available with High-Performance Models) □ Exhaust Fan (Only available with High-Performance Models) □ U/L Inspection □ CSA Inspection 		Auxiliary Hose Access Port
 Exhaust Fan (Only available with High-Performance Models) U/L Inspection CSA Inspection 		o Quantity Size
□ U/L Inspection□ CSA Inspection		Zero Speed Switch for Fans (Only available with High-Performance Models)
☐ CSA Inspection		Exhaust Fan (Only available with High-Performance Models)
		U/L Inspection
		CSA Inspection
Other Requirements:		Other Requirements:



15. Will t	he equipment be installed in the USA or be exported?		USA	Exported
a.	If exported, please provide shipping port			
b.	If exported, do you require export crating?		Yes	No
C.	Do you require a freight quote?		Yes	No
d.	If a freight quote is requested, please provide a shipping addr	ess:		
	☐ Same address as above			
	Address:			
	City, State, or Province:			
	Zip or Postal Code:			
	Country:			
Please p	rovide any additional information, requirements, or questic	ns:		

Thank you for this opportunity!